

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strikethrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

1. (Currently Amended) An optical communication apparatus, comprising:

an optical tunable filter, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting signal light with a specific wavelength from signal light multiplexed using wavelength-division multiplexing (WDM);
 a detection unit detecting signal light extracted by the optical tunable filter; and
 a control signal generating unit generating the control signal needed to enable the optical tunable filter to extract the signal light with a predetermined wavelength by the detection unit, based on a detected result obtained by scanning a wavelength transmission characteristic of the optical tunable filter for a range of a wavelength band including all of the multiplexed signal light;
wherein the control signal generating unit determines existence of a signal light where a peak level of a detected light is greater than a given signal light level and a peak point of the detected light at a determined peak width from the peak level of the detected light is less than a predetermined level.

~~wherein the control signal applied to the optical tunable filter for extracting each multiplexed signal light is known for each signal light by the detected result, and the control signal generating unit generating the control signal by using the control signal applied to the optical tunable filter when the detection unit detects the signal light in scanning of the wavelength transmission characteristic.~~

2. (Previously Presented) The optical communication apparatus according to claim 1, wherein said control signal generating unit generates the control signal needed to extract the signal light with a desired wavelength, based on both the detected result and information indicating a current operating situation of the multiplexed signal light.

3. (Currently Amended) An optical communication apparatus, comprising:

an optical tunable filter, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting signal light with a specific wavelength from signal light multiplexed using wavelength-division multiplexing (WDM);

Amendment
has
been
entered
2-3-08
LP

a detection unit detecting signal light extracted by the optical tunable filter;
an operation unit operating to generate information for designating the control signal needed to enable the optical tunable filter to extract signal light with a designated wavelength, based on a detected result of two signal lights at each edge of the wavelength band obtained by scanning the detection unit when scanning a wavelength transmission characteristic of the optical tunable filter for a range from outside of a wavelength band including all of the multiplexed signal light; and

a control signal generating unit generating the control signal according to the designation information; and wherein the control signal applied to the optical tunable filter for extracting each multiplexed signal light is computed by interpolation operation based on the control signal applied to the optical tunable filter, a wrong extraction of a signal with a different wavelength is avoided when extracting a signal with a desired wavelength, and

~~the control signal generating unit generating the control signal by using the control signal applied to the optical tunable filter when the detection unit detects the signal light in scanning of the wavelength transmission characteristic.~~

wherein the control signal generating unit determines existence of a signal light where a peak level of a detected light is greater than a given signal light level and a peak point of the detected light at a determined peak width from the peak level of the detected light is less than a predetermined level.

4. (Previously Presented) The optical communication apparatus according to claim 3, wherein said operation unit executes the computation, based on both the detected result and information indicating a current operating situation of the multiplexed signal light.

5. (Withdrawn) An optical communication system, comprising:
an optical tunable filter, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting signal light with a specific wavelength from signal light multiplexed by a wavelength-division multiplexing (WDM) method;
a detection unit detecting signal light extracted by the optical tunable filter;
an optical wavelength detecting unit detecting signal light with a specific wavelength of all segments of signal light extracted by the optical tunable filter;
an operation unit operating to generate information for designating the control signal needed to enable the optical tunable filter to extract signal light with a designated wavelength, based on both a detected result of the detection unit and the optical wavelength detecting unit and information indicating a current operating situation of the multiplexed signal light; and
a control signal generating unit generating the control signal according to the designation

information.

6. (Withdrawn) An optical communication system, comprising:
- an optical tunable filter, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting signal light with a specific wavelength from signal light multiplexed by a wavelength-division multiplexing (WDM) method;
 - a detection unit detecting signal light extracted by the optical tunable filter;
 - a reference signal light detecting unit detecting reference signal light that is known to be always included in signal light inputted to the optical tunable filter of all segments of signal light extracted by the optical tunable filter;
 - an operation unit operating to generate information for designating the control signal needed to enable the optical tunable filter to extract signal light with a predetermined wavelength, based on both a detected result of the detection unit and a detected result of the reference signal light detecting unit; and
 - a control signal generating unit generating the control signal according to the designation information.

7. (Withdrawn) The optical communication system according to claim 5, wherein said optical wavelength detecting unit performs the detection of signal light with a specific wavelength of the multiplexed signal light.

8. (Withdrawn) The optical communication system according to claim 5, wherein said optical wavelength detecting unit comprises a periodic filter whose free spectrum range (FSR) is the same as a wavelength interval between two segments of adjacent signal light of the multiplexed signal light and whose peak of a wavelength transmission characteristic coincides with a wavelength of the signal light.

9. (Withdrawn) The optical communication system according to claim 8, wherein full width at half maximum (FWHM) and finesse of said periodic filter are between 0.1nm and 0.3nm and between 3 and 8, respectively.

10. (Withdrawn) The optical communication system according to claim 8, further comprising a control unit controlling a change of wavelength transmission characteristic of said optical tunable filter in such a way as to increase amount of light of signal light that transmits said periodic filter.

11. (Withdrawn) An optical communication system, comprising:
- an optical tunable filter, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting signal light with a specific wavelength from signal light multiplexed by a wavelength-division multiplexing (WDM) method;
 - an optical wavelength detecting unit detecting signal light with a specific wavelength of all segments of signal light extracted by the optical tunable filter;
 - an operation unit operating to generate information for designating the control signal needed to enable the optical tunable filter to extract signal light with a predetermined wavelength, based on both a detected result of the light detection unit and information indicating a current operating state of the multiplexed signal light; and
 - a control signal generating unit generating the control signal according to the designation information.
12. (Withdrawn) The optical communication system according to claim 5, wherein
- said optical wavelength detecting unit comprises a periodic filter and
 - said operation unit operates to generate information for designating the control signal needed to enable the optical tunable filter to extract signal light with a designated wavelength, based on detected results of two segments of signal light at each edge of the wavelength band that is transmitted through the periodic filter and is obtained by shifting when shifting the wavelength transmission characteristic of the optical tunable filter from outside a wavelength band including all segments of the multiplexed signal light.
13. (Previously Presented) The optical communication apparatus according to claim 3, wherein when receiving no instruction to extract signal light, said operation unit operates to generate in advance the designation information needed to select and extract one arbitrary segment of signal light from the multiplexed signal light, and when receiving the instruction later, said operation unit operates to generate the control signal needed to extract the designated signal light, based on information obtained up to then.
14. (Previously Presented) The optical communication apparatus according to claim 3, wherein when an instruction to extract signal light is modified, said operation unit operates to generate the designation information needed to extract modified designated signal light, based on information obtained prior to the reception of the modified instruction.
15. (Previously Presented) The optical communication apparatus according to claim 3, wherein when determining the existence/non-existence of signal light, based on a detected

result of said detection unit, said operation unit sets a reference of the determination, based on a signal level detected by said detection unit when a wavelength transmission characteristic of said optical tunable filter is set so that signal light with a wavelength located outside a wavelength band including all segments of the multiplexed signal light can be transmitted.

16. (Previously Presented) The optical communication apparatus according to claim 15, wherein when determining the existence/non-existence of signal light, based on a detected result of said detection unit, said operation unit determines a target signal not to be signal light if the size of a target signal level is less than the predetermined value.

17. (Previously Presented) The optical communication apparatus according to claim 16, wherein said operation unit maintains a maximum signal level of signal light detected by the shift of said detection unit when shifting the wavelength transmission characteristic of said optical tunable filter in a range where the size of a target signal level exceeds the predetermined value, and if said detection unit detects the decrease of a signal level from the maximum value by more than a predetermined value when continuing to scan the wavelength transmission characteristic in a predetermined range after detecting the maximum value, said operation unit regards the control signal generated by said control signal generating unit when detecting the maximum value as an optimal control signal to be applied to said optical tunable filter to extract the signal light, and performs the computation.

18. (Withdrawn) The optical communication system according to claim 5, wherein when receiving no instruction to extract signal light, said operation unit operates to generate in advance the designation information needed to select and extract one arbitrary segment of signal light from the multiplexed signal light, and when receiving the instruction later, said operation unit operates to generate the control signal needed to extract the designated signal light, based on information obtained up to then.

19. (Withdrawn) The optical communication system according to claim 5, wherein when the instruction to extract signal light is modified, said operation unit operates to generate the designation information needed to extract modified designated signal light, based on information obtained prior to the reception of the modified instruction.

20. (Withdrawn) The optical communication system according to claim 5, wherein when determining the existence/non-existence of signal light, based on a detected result of said detection unit, said operation unit sets a reference of the determination, based on a signal level

detected by said detection unit when a wavelength transmission characteristic of said optical tunable filter is set so that signal light with a wavelength located outside a wavelength band including all segments of the multiplexed signal light can be transmitted.

21. (Withdrawn) The optical communication system according to claim 20, wherein when determining the existence/non-existence of signal light, based on a detected result of said detection unit, said operation unit determines a target signal not to be signal light if the size of a target signal level is less than the predetermined value.

22. (Withdrawn) The optical communication system according to claim 21, wherein said operation unit maintains a maximum signal level of signal light detected by the shift of said detection unit when shifting the wavelength transmission characteristic of said optical tunable filter in a range where the size of a target signal level exceeds the predetermined value, and if said detection unit detects the decrease of a signal level from the maximum value by more than a predetermined value when continuing to shift the wavelength transmission characteristic in a predetermined range after detecting the maximum value, said operation unit regards the control signal generated by said control signal generating unit when detecting the maximum value as an optimal control signal to be applied to said optical tunable filter to extract the signal light and performs the computation.

23. (Currently Amended) A method for controlling an optical tunable filter, comprising: detecting a signal light extracted by the optical tunable filter with a detection unit, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting the signal light with a specific wavelength from signal light multiplexed by wavelength-division multiplexing (WDM); and

generating the control signal needed to enable the optical tunable filter to extract the signal light with a predetermined wavelength, based on the detected result obtained by scanning the wavelength transmission characteristic of the optical tunable filter in a wavelength band including all segments of the multiplexed signal light and wherein the control signal applied to the optical tunable filter for extracting each multiplexed signal light is known for each signal light by the detected result, wherein

the control signal generating determines existence of a signal light where a peak level of a detected light is greater than a given signal light level and a peak point of the detected light at a determined peak width from the peak level of the detected light is less than a predetermined level

the control signal is generated by using the control signal applied to the optical

tunable filter when the detection unit detects the signal light in scanning of the wavelength transmission characteristic.

24. (Currently Amended) A method for controlling an optical tunable filter, comprising:
detecting a signal light extracted by the optical tunable filter with a detection unit, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting the signal light with a specific wavelength from signal light multiplexed by wavelength-division multiplexing (WDM);

generating information for designating the control signal needed to enable the optical tunable filter to extract the signal light with a designated wavelength, based on a detected result of two segments of signal light at each edge of the wavelength band obtained by the detecting result when scanning a wavelength transmission characteristic of the optical tunable filter from outside a wavelength band including all segments of the multiplexed signal light; and

generating the control signal according to the designation information and wherein the control signal applied to the optical tunable filter for extracting each multiplexed signal light is known for each signal light by the detected result, wherein

the control signal generating determines existence of a signal light where a peak level of a detected light is greater than a given signal light level and a peak point of the detected light at a determined peak width from the peak level of the detected light is less than a predetermined level

~~the control signal is generated by using the control signal applied to the optical tunable filter when the detection unit detects the signal light in scanning of the wavelength transmission characteristic.~~

25. (Withdrawn) A method for controlling an optical tunable filter, comprising:
performing the first detection of detecting signal light extracted by the optical tunable filter, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting signal light with a specific wavelength from signal light multiplexed by a wavelength-division multiplexing (WDM) method;

performing the second detection of detecting signal light with a specific wavelength of all segments of signal light extracted by the optical tunable filter;

generating information for designating the control signal needed to enable the optical tunable filter to extract signal light with a designated wavelength, based on both the detected results of the first and second detection and information indicating a current operating situation of the multiplexed signal light; and

generating the control signal according to the designation information.

26. (Withdrawn) A method for controlling an optical tunable filter, comprising:
detecting signal light extracted by the optical tunable filter, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting signal light with a specific wavelength from signal light multiplexed by a wavelength-division multiplexing (WDM) method;
detecting reference signal light that is known to be always included in signal light inputted to the optical tunable filter of all segments of signal light extracted by the optical tunable filter;
generating information for designating the control signal needed to enable the optical tunable filter to extract signal light with a predetermined wavelength, based on both a detected result of the signal light and a detected result of the reference signal light; and
generating the control signal according to the designation information.

27. (Currently Amended) A method for controlling an optical tunable filter, comprising:
detecting signal light with a specific wavelength of all segments of signal light extracted by the optical tunable filter with a detection unit, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting signal light with a specific wavelength from signal light multiplexed by wavelength-division multiplexing (WDM);
generating information for designating the control signal needed to enable the optical tunable filter to extract the signal light with a predetermined wavelength, based on both the detected result and information indicating a current operating state of the multiplexed signal light;
and

generating the control signal according to the designation information and wherein the control signal applied to the optical tunable filter for extracting each multiplexed signal light is known for each signal light by the detected result, wherein

the control signal generating determines existence of a signal light where a peak level of a detected light is greater than a given signal light level and a peak point of the detected light at a determined peak width from the peak level of the detected light is less than a predetermined levelthe control signal is generated by using the control signal applied to the optical tunable filter when the detection unit detects the signal light in scanning of the wavelength transmission characteristic.

28. (Currently Amended) An optical communication apparatus, comprising:
an optical tunable filter, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting signal light with a specific wavelength from a signal light multiplexed by wavelength-division multiplexing (WDM);

detection means detecting the signal light extracted by the optical tunable filter; and
control signal generating means generating the control signal needed to enable the optical tunable filter to extract the signal light with a predetermined wavelength by the detection means, based on a detected result obtained by scanning a wavelength transmission characteristic of the optical tunable filter in a wavelength band including all segments of the multiplexed signal light and wherein the control signal applied to the optical tunable filter for extracting each multiplexed signal light is known for each signal light by the detected result-, and wherein the control signal generating means determines existence of a signal light where a peak level of a detected light is greater than a given signal light level and a peak point of the detected light at a determined peak width from the peak level of the detected light is less than a predetermined level~~the control signal generating means generating the control signal by using the control signal applied to the optical tunable filter when the detection means detects the signal light in scanning of the wavelength transmission characteristic.~~

29. (Currently Amended) An optical communication apparatus, comprising:
an optical tunable filter, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting signal light with a specific wavelength from a signal light multiplexed by wavelength-division multiplexing (WDM);
detection means detecting the signal light extracted by the optical tunable filter;
operation means operating to generate information for designating the control signal needed to enable the optical tunable filter to extract the signal light with a designated wavelength, based on a detected result of two segments of signal light at each edge of the wavelength band obtained by scanning of the detection means when shifting a wavelength transmission characteristic of the optical tunable filter from outside a wavelength band including all segments of the multiplexed signal light; and
control signal generating means generating the control signal according to the designation information and wherein the control signal applied to the optical tunable filter for extracting each multiplexed signal light is known for each signal light by the detected result-, and wherein the control signal generating means determines existence of a signal light where a peak level of a detected light is greater than a given signal light level and a peak point of the detected light at a determined peak width from the peak level of the detected light is less than a predetermined level~~the control signal generating means generating the control signal by using the control signal applied to the optical tunable filter when the detection means detects the signal light in scanning of the wavelength transmission characteristic.~~

30. (Withdrawn) An optical communication system, comprising:

an optical tunable filter, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting signal light with a specific wavelength from signal light multiplexed by a wavelength-division multiplexing (WDM) method;

detection means for detecting signal light extracted by the optical tunable filter;

optical wavelength detecting means for detecting signal light with a specific wavelength of all segments of signal light extracted by the optical tunable filter;

operation means for operating to generate information for designating the control signal needed to enable the optical tunable filter to extract signal light with a designated wavelength, based on both a detected result of the detection means and the optical wavelength detecting means and information indicating a current operating situation of the multiplexed signal light; and

control signal generating means for generating the control signal according to the designation information.

31. (Withdrawn) An optical communication system, comprising:

an optical tunable filter, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting signal light with a specific wavelength from signal light multiplexed by a wavelength-division multiplexing (WDM) method;

detection means for detecting signal light extracted by the optical tunable filter;

reference signal light detecting means for detecting reference signal light that is known to be always included in signal light inputted to the optical tunable filter of all segments of signal light extracted by the optical tunable filter;

operation means for operating to generate information for designating the control signal needed to enable the optical tunable filter to extract signal light with a predetermined wavelength, based on both a detected result of the detection means and a detected result of the reference signal light detecting means; and

control signal generating means for generating the control signal according to the designation information.

32. (Withdrawn) An optical communication system, comprising:

an optical tunable filter, whose wavelength transmission characteristic varies depending on a control signal, transmitting and extracting signal light with a specific wavelength from signal light multiplexed by a wavelength-division multiplexing (WDM) method;

optical wavelength detecting means for detecting signal light with a specific wavelength of all segments of signal light extracted by the optical tunable filter;

operation means for operating to generate information for designating the control signal needed to enable the optical tunable filter to extract signal light with a predetermined

wavelength, based on both a detected result of the optical detection means and information indicating a current operating state of the multiplexed signal light; and
control signal generating means for generating the control signal according to the designation information.

33. (Currently Amended) An optical communication apparatus, comprising:
an optical tunable filter for passing a wavelength division multiplexed light signal and having an adjustable wavelength passing range responsive to a range adjustment signal;
a detector detecting the light signal from the filter; and
a control unit producing the adjustment signal adjusting the range of the filter responsive to the light signal detected and a designated wavelength of a wavelength division multiplexed light signal to be extracted and determining existence of the light where a peak level of a detected light is greater than a predetermined signal light level and a peak point of the detected light at a determined peak width from the peak level of the detected light is less than a predetermined peak level,
the control unit generating the control signal by using the control signal applied to the optical tunable filter when the detector detects the signal light in scanning of a wavelength transmission characteristic.

34. (Currently Amended) An optical communication method, comprising:
detecting an output light signal from an optical tunable filter using a detection unit for a wavelength division multiplexed light signal and having an adjustable wavelength passing range responsive to a range adjustment signal where the detecting determining existence of the light where a peak level of a detected light is greater than a predetermined signal light level and a peak point of the detected light at a determined peak width from the peak level of the detected light is less than a predetermined peak level; and
producing the adjustment signal using an adjustment signal generating unit adjusting the range of the filter responsive to the detected output light signal and a designated wavelength of a wavelength division multiplexed light signal to be extracted, wherein
the adjustment signal generating unit generating the adjustment signal by using the adjustment signal applied to the optical tunable filter when the detection unit detects the light signal in scanning of a wavelength transmission characteristic.